



# T-NUTS, STRAIGHT BARREL

# 4 Prongs

4 Prong T-Nuts can be used in hard and soft woods. Also available in Hopper Feed style for labor-saving automation.

Also available in metric sizes noted.



Part Number	Thread Size	A Flange Diameter	B Barrel Height	C Barrel Diameter	D Prong Height	T Material Thickness	Drill Size	Lbs./M	Pcs. Ctn. M
63264	6-32	9/16	3/8	.162	9/64	.024	11/64	4	15
83244	8-32	23/32	1/4	.209	3/16	.031	7/32	5	5
M407064	M4xP0.7	18.3	6.4	5.3	4.8	0.8	5.6		
102444	10-24	3/4	9/32	.243	3/16	.039	1/4	7	5
102454	10-24	3/4	5/16	.243	7/32	.039	1/4	7	5
102454F11	10-24	45/64	5/16	.243	3/16	.039	1/4	7	5
103244	10-32	3/4	9/32	.243	3/16	.039	1/4	7	5
103254	10-32	3/4	5/16	.243	7/32	.039	1/4	7	5
M508084	M5xP0.8	19.7	7.9	6.2	5.6	1.0	6.4		
103254F11	10-32	45/64	5/16	.243	3/16	.039	1/4	7	5
103254F20*	10-32	1-1/4	5/16	.243	7/32	.039	1/4	8	2.5
142034	1/4-20	3/4	3/16	.305	7/64	.047	5/16	8	5
142054 <sup>1</sup>	1/4-20	3/4	5/16	.305	15/64	.047	5/16	9	5
M610084	M6xP1.0	19.7	7.9	7.5	6.0	1.2	7.9		
142054F20	1/4-20	1-1/4	5/16	.305	15/64	.047	5/16	20	2
142054S	1/4-20	3/4	5/16	.305	9/64	.047	5/16	9	5
142054T	1/4-20	3/4	5/16	.305	7/32	.043	5/16	8	5
M610084T	M6xP1.0	19.7	7.9	7.5	5.6	1.1	7.9		
142074	1/4-20	3/4	7/16	.305	15/64	.047	5/16	9	5
M610114	M6xP1.0	19.7	11.1	7.7	6.0	1.2	7.9		
142074F20	1/4-20	1-1/4	7/16	.305	5/16	.047	5/16	20	2
142074T	1/4-20	3/4	7/16	.305	1/4	.043	5/16	9	5
M610114T	M6xP1.0	19.7	11.1	7.5	6.4	1.1	7.9		
142094	1/4-20	3/4	9/16	.305	1/4	.047	5/16	11	4
M610144	M6xP1.0	19.7	14.3	7.5	6.4	1.2	7.9		
142094F20	1/4-20	1-1/4	9/16	.305	1/4	.047	5/16	22	1.5

\* New Tooling

<sup>1</sup> Available in Stainless Steel. (See page TN - 44.)



# T-NUTS, STRAIGHT BARREL

# 4 Prongs

Part Number	Thread Size	A Flange Diameter	B Barrel Height	C Barrel Diameter	D Prong Height	T Material Thickness	Drill Size	Lbs./M	Pcs. Ctn. M
1420144	1/4-20	3/4	7/8	.305	1/4	.047	5/16	15	2.5
142854T	1/4-28	3/4	5/16	.305	7/32	.043	5/16	8	5
561864 <sup>1</sup>	5/16-18	7/8	3/8	.390	1/4	.063	25/64	14	2.5
<i>M813104</i>	<i>M8 x P1.25</i>	22.2	9.5	9.9	6.4	1.6	9.9		
561864F20*	5/16-18	1-1/4	3/8	.390	1/4	.063	25/64	14	2.5
561864T	5/16-18	7/8	3/8	.370	9/32	.055	3/8	14	2.5
<i>M813104T</i>	<i>M8 x P1.25</i>	22.2	9.5	9.4	7.1	1.4	9.5		
561864E	5/16-18	7/8	3/8	.370	1/4	.051	3/8	14	2.5
<i>M813104E</i>	<i>M8 x P1.25</i>	22.2	9.5	9.4	6.4	1.3	9.5		
561864TF12	5/16-18	3/4	3/8	.370	1/4	.059	3/8	16	2.5
561884T	5/16-18	7/8	1/2	.370	1/4	.059	3/8	15	2.5
5618104	5/16-18	7/8	5/8	.390	1/4	.063	25/64	19	2.5
5618104F20*	5/16-18	1-1/4	5/8	.390	1/4	.063	25/64	21	1.5
5618104T	5/16-18	7/8	5/8	.370	5/16	.055	3/8	17	2.5
<i>M813164T</i>	<i>M8 x P1.25</i>	22.2	15.9	9.4	7.9	1.4	9.5		
5618104E	5/16-18	7/8	5/8	.370	1/4	.051	3/8	17	2.5
<i>M813164E</i>	<i>M8 x P1.25</i>	22.2	15.9	9.4	6.4	1.3	9.5		
5618144T	5/16-18	7/8	7/8	.370	1/4	.059	3/8	21	2
381674 <sup>1</sup>	3/8-16	1	7/16	.460	5/16	.071	15/32	22	2
381674T	3/8-16	1	7/16	.440	5/16	.063	29/64	19	2
<i>M1015114T</i>	<i>M10 x P1.5</i>	25.4	11.1	11.5	7.9	1.6	11.5		
382474T	3/8-24	1	7/16	.440	5/16	.063	29/64	19	2
121364	1/2-13	1-1/4	3/8	.591	7/32	.091	19/32	39	1
121364L	1/2-13	1-1/4	3/8	.591	5/16	.091	19/32	39	1
581164	5/8-11	1-7/16	3/8	.720	1/4	.091	23/32	49	1

\* New Tooling                      <sup>1</sup>Available in Stainless Steel. (See page TN - 44.)

If Crimp Lock is desired, please refer to Crimp Lock on page TN - 14.  
 Most 4 - prong T-Nuts can be made with a Crimp Lock.